

ELECTRONIC SYSTEM, COMPONENTS  
AND METHOD FOR TRACKING FILES

CROSS-REFERENCE TO RELATED APPLICATION

5 This application is a continuation of United States Patent Application No. 08/379,944  
filed on January 27, 1995, entitled ELECTRONIC SYSTEM, COMPONENTS AND  
METHOD FOR TRACKING FILES, the entire disclosure of which is incorporated herein by  
reference.

BACKGROUND OF THE INVENTION

10 In general, the present invention relates to an electronic system, hardware, and  
method for tracking the location of files and their containers. More specifically, the present  
invention relates to an electronic file tracking system that maintains a database identifying  
each file and its current location by interactive communication between a computer processor  
and the file folders. The invention is particularly adapted for use with office furniture.

15 In a typical office environment, files are normally stored in various file cabinets  
located throughout the office. Each file cabinet or group of file cabinets stores files  
belonging to a particular category. These files are typically organized in an alphabetical or  
numerical order within the drawers of the file cabinet or group of file cabinets. Files may  
also be stored on or in various shelving units, trays, boxes, work surfaces, bins,  
compartments, tables, desk drawers, or carts. In order to make these files accessible to all  
20 office personnel, the files must be stored in an organized manner. Office personnel expend a  
substantial amount of time retrieving files, replacing files back into the file cabinets, and  
maintaining the organization of the files.

When someone wishes to obtain a particular file, he or she must determine in which office, which file cabinet, and which drawer of the file cabinet the file is supposed to be located. If the person looking for the file does not know the location of the file first hand, he or she must make inquiries to the other employees or check a manually maintained listing of the file organization to locate the file. Once this person identifies where the file is supposed to be located, the person must search through the numerous files stored in the drawer to determine if the file is actually located in the drawer. In searching through the file cabinet drawer, this person may discover that the file is not located where it was supposed to be. The person must then again inquire about the office to determine if someone else has the file and, if no one else has the file, this person must search through other file drawers to determine if the file is misfiled or lost. Active files tend to become stacked on the desktops of the employees most recently using those particular files, leading to poor accessibility for others. Clearly, tracking down a file may consume a significant portion of an employee's time and any time spent looking for or reorganizing files is an inefficient use of that employee's time.

To maintain an organized system, when someone must add a number of new files to a particular drawer of a file cabinet that is already filled to capacity, he or she must shift those files in the back of the drawer to another drawer, which may also be filled to capacity. Further, whenever a sequential ordering scheme is used to organize files, even frequently accessed files may be dispersed throughout a number of drawers rather than in the front of a single file drawer where the frequently accessed files would be more easily accessible.

a

The above problems are particularly prevalent in hospitals, <sup>doctor's</sup> ~~doctors~~ offices, law

offices, government agencies, and anywhere else where large amounts of printed documents or other media are handled and maintained.

5

One approach that was developed to alleviate some of the above problems in tracking files is to provide a bar code label on each file folder and to maintain a database correlating the bar code I.D. of the file and its relative location. In order to accurately maintain the file locations in the database, bar code readers are placed about the office for employees to scan the bar code and enter a new location whenever the employees move a file from one location to another.

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198

returned, and determines when a new file has been added to the system. Additionally, the file tracking system of the present invention allows users to easily and accurately identify the exact location of a file by having a processor communicate with a device carried by the file folders and activate an indicator, such as a light, on the file folders and/or file cabinets in response to a signal sent by the processor. Thus, the present invention requires minimal human interaction to maintain an accurate database identifying the location of the files while permitting both random and ordered filing of the file folders. Moreover, the file tracking system of the present invention may be inexpensively and readily implemented in existing office furniture.

Additional features and advantages of the invention will be set forth in part in the description which follows and in part will be apparent from the description, or may be learned by practice of the invention.

The features and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages, and in accordance with the purpose of the invention as embodied and broadly described herein, the file tracking system of this invention includes a database for maintaining at least file identity, file location, and unique file address for a plurality of files, a processor for interfacing with the database and issuing control signals, a bus connected to the processor, a folder retainer connected to the processor by the bus, a plurality of file folders, each file folder including an addressable device adapted to be electrically connected to the bus when the file folder is placed in the folder retainer. Each

folder may include an indicator which is activated when the addressable device receives a control signal from the processor including the unique address corresponding to the file folder. The database may additionally store the following: access information, which may be used to prevent individuals from accessing certain file folders; retention information, which may be used to determine the length of time since the file folder was last accessed in order to determine whether the file may be purged; classification information, which may indicate any classification groups the file folder is associated with; access history, which may indicate who checked out the file folder and when the file folder was checked in or out; key word lists, which list certain key words that describe or may be found in the file; and location history information, which may indicate the locations and dates at which the file folder has been located over a period of time.

The above features and advantages may also be attained by using the file cabinet of the present invention in a file tracking system. The file cabinet of the present invention includes a plurality of file drawers, at least one file drawer including a first conductor for providing control signals a file folder when the file folder is placed in the file drawer, the control signals being provided by the file tracking system, and a second conductor for providing a return path from the file folder placed in the file drawer.

Additionally, the advantages of the present invention may be attained by using a file folder of the present invention in a file tracking system. The file folder of the present invention includes at least one surface, an addressable device carried by the file folder and having a unique address, a first conductor on the surface electrically coupled to the addressable device for providing control signals to the addressable device when the file folder

is placed in a folder retainer, the first conductor adapted to communicatively couple to a processor of the file tracking system, the control signals being provided by the processor, and a second conductor on the surface for providing a return path from the addressable device.

5           These and other features, objects, and benefits of the invention will be recognized by those who practice the invention and by those skilled in the art, from the specification, the claims, and the drawing figures.

#### BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

10           Fig. 1 is a pictorial view of a file tracking system constructed in accordance with a first embodiment of the present invention;

          Fig. 2 is a block diagram illustrating the hierarchy of the file tracking system of the present invention;

15           Fig. 3 is an electrical schematic view illustrating the electrical connections of a portion of the file tracking system shown in Fig. 1;

          Fig. 4 is an electrical schematic view of an addressable switch which may be used in the file tracking system of the present invention;

          Fig. 5 is a perspective view of a file folder in electrical contact with a bus conductor according to a first implementation in the file tracking system of the present invention;

20           Fig. 6 is a perspective view of a file folder and a bus conductor according to a second implementation in the file tracking system of the present invention;

Fig. 7 is a perspective view of a hanging file folder in electrical contact with a bus conductor according to a third implementation in the file tracking system of the present invention;

Fig. 8 is a graphic view of a main user interface window of the file tracking system of the present invention;

Fig. 9 is a graphic representation of a debug window of the file tracking system of the present invention;

Fig. 10 is a graphic representation of a Get Number dialog box of the file tracking system of the present invention;

Fig. 11 is a flow chart illustrating the polling operation of the file tracking system of the present invention;

Fig. 12 is flow chart showing the device scanning operation of a subroutine executed by the file tracking system of the present invention;

Fig. 13 is a flow chart showing the indicator light scanning operation of the file tracking system of the present invention;

Fig. 14 is a pictorial view of a file tracking system constructed in accordance with a second embodiment of the present invention; and

Fig. 15 is a pictorial view of a file tracking system constructed in accordance with a third embodiment of the present invention.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the present preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings.

The exemplary embodiment of the file tracking system of the present invention is shown in Fig. 1 and is designated generally by the reference numeral 10. As used throughout this description of the invention and in the following claims the term "media" includes paper, film, X-ray film, magazines, books, photographs, microfiche, video and audio tapes, models, exhibits, or anything else retained and filed. The term "file folders" refers to any type of structure for containing media including bi-fold, side-tab, expandable, and tri-fold file folders, and may further include various types of binders, jackets, envelopes, boxes, holders, cartons or the like. The term "files" as used herein includes the file folder and all media inside. The term "folder retainers" refers to various numbers of, and/or combinations of, file trays, file cabinets, shelving units, desks, furniture drawers, packing boxes, archive tubs, wall-mounted or countertop file racks, bins, carts, pads, mats, desk tops, countertops, any work surface on which file folders are commonly stacked or placed, or any other structure for holding file folders. A "file locating device" broadly includes any device that would assist a user to locate a file. An "annunciator" is a file locating device that audibly and/or visually announces the location of a file, and includes audible alarms, such as beepers, and visual indicators, such as light emitting diodes (LEDs). Additionally, other types of annunciators or, as more broadly defined herein, file locating devices, such as an audible alarm, may supplement or replace the visual indicator lights used in the file tracking system.

In general, file tracking system 10 includes a processor 20 and a plurality of folder retainers. For purposes of example, Fig. 1 shows a file tray 40, a file cabinet 50, a shelving



unit 60, and a desk 85 although any of the above defined folder retainers may be used in various numbers and combinations.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995  
1000

A bus 30 communicatively couples processor 20 with the folder retainers. Each folder retainer includes bus conductors 80 for electrically contacting one or more file folders 70. Bus 30 preferably includes two lines. One for providing control signals to file folders 70 and another for providing a return. Although the preferred embodiment utilizes two lines, bus 30 may be implemented in any bus using any number of physical or virtual, multiplexed lines. Bus conductors 80 may be included on a surface of a file retainer such as a file drawer, or embedded within a working surface, such as a desktop, countertop, shelf, or tray, to create a file retainer location thereon.

Processor 20 includes a display 22 and an input device 25, such as a keyboard. Preferably, processor 20 is a personal computer. As will be explained in greater detail below, processor 20 maintains and interfaces with a database under the direction of an operating program that instructs processor 20 to actively communicate with the folder retainers and the file folders 70 via bus 30. In this manner, processor 20 may update the database and maintain accurate information on the location of file folders 70 placed in the system. The database used may be any commercially available ANSI SQL compatible database, such as Microsoft Access™ database.

20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995  
1000

A tray 40, which is useful in the file tracking system 10 of the present invention, may be formed of a conventional file tray modified to include a bus conductor 80 having at least two conductive strips (42, 43), an indicator light 45, such as a light emitting diode (LED), and an addressable switch 100 (Fig. 4), which is connected between the conductive strips and

indicator light 45. Preferably, the conductive strips include at least one ground conductor 42 and at least one control conductor 43 connected to bus 30. As will be described in greater detail below, tray 40 provides a communication link between file folders 70, which are placed thereon to processor 20 whereby processor 20 can track the location of file folders 70 placed on file tray 40 and can selectively light indicator light 45 on tray 40 and any indicator light 75 on file folders 70.

File cabinet 50 includes a plurality of drawers 54a-54c, each of which includes an indicator light 55a-55c on an outer drawer face. Each drawer 54a-54c further includes a bus conductor 80 having at least one ground conductor 52 and a control conductor 53, which contact the conductive strips of file folders 70, and an addressable drawer switch 100 (Fig. 4), which is connected between ground conductor 52, control conductor 53, and indicator light 55a-55c. File cabinet 50 may optionally include a branch indicator 95 (Fig. 3) associated with a branch control point 92 (Fig. 2) and having a unique cabinet address and an indicator light 51 that can be lit whenever processor 20 transmits a control signal including the unique cabinet address of the addressable cabinet switch.

Shelving unit 60 includes at least one shelf 61a-61b, which includes a bus conductor 80 having at least one ground conductor 62 and a control conductor 63 for contacting the conductive strips of file folders 70. Shelving unit 60 also preferably includes an addressable switch 100 having a unique address and an indicator light 65, which can be lit whenever processor 20 transmits a control signal including the unique address of the addressable switch.

Desk 85 includes at least one drawer 86a, 86b which includes a bus conductor 80 therein and an indicator 87a, 87b on an outer face thereof. In addition, desk 85 may include a bus conductor 80 embedded in a work surface thereof. Further, a mat 88 having a bus conductor 80 embedded therein may be placed on the top of desk 85 or any other working surface of an article of furniture.

Fig. 2 illustrates a typical system hierarchy employed when several branch connections exist in the system. A user's work area 90 may include, for example, a processor 20 and a plurality of file cabinets 50. Because each file cabinet 50 includes a plurality of drawers 54a-54c, which, in turn, contain a plurality of file folders 70, file tracking system 10 preferably utilizes the hierarchy shown in Fig. 2 to separately activate a single branch at a time. To enable a single branch to be activated at a time, file tracking system 10 preferably includes a plurality of branch control points 92, 92', which may be individually activated to permit access to the branch controlled by the branch control point 92. Thus, to access file folders 70 in a drawer 54a of file cabinet 50a, processor 20 transmits a control signal to the branch control point 92 for the file cabinet 50a such that processor 20 may now transmit a control signal to the branch control point 92' for drawer 54a. After processor 20 transmits a control signal to branch control point 92 for cabinet 50a, processor 20 transmits a control signal to the branch control point 92' for drawer 54a to activate the bus conductors 80 located in drawer 54a thereby allowing processor 20 to communicate with file folders 70 included in file drawer 54a. Alternatively, a processor 20 that is located outside user's work area 90 may access file folders 70 within user's work area 90 by transmitting control signals through a network 91. File tracking system 10 may

further include a serial port adaptor or secondary processor 27, which is connected to receive control signals from a serial port of processor 20, convert the received control signals to a format appropriate for a single pair bus, and distribute the control signals to the correct file cabinet 50 or other folder retainer connected to the system.

5           Fig. 3 shows an exemplary electrical schematic of the connections between processor 20 and file folders 70. As shown in Fig. 3, bus 30 includes a control line 31 and a ground line 32. Bus 30 is preferably a single pair bus. In the hierarchical arrangement shown in Fig. 3, branch control point switch assemblies 93a and 93b represent control points for activating the bus conductors 80 of two different file drawers 54 of a file cabinet 50.

10           Although only one file folder (70a, 70b) is shown for each file drawer 54, each file drawer 54 will typically have a plurality of file folders 70 contacting its bus connector 80.

15           Each file folder 70 preferably includes a folder indicator light 75 and an addressable folder switch 76 having a unique address associated therewith. Alternatively, each folder may include an addressable device when an indicator is not employed such that each folder has a unique ID tag that may be communicated to processor 20. Although the file folders 70 are illustrated as bi-fold file folders, as stated above, the file folders may be any type of file folder as previously defined.

20           Fig. 4 shows the general structure of an addressable switch 100 useful in the file tracking system of the present invention. Addressable switch 100 includes a load transistor 101 having a gate 102, a source serving as a load terminal 103, and a drain serving as a ground terminal 104. Addressable switch 100 further includes a digital control device 105 connected between gate 102 and a control terminal 106. Digital control device 105 includes

a read only memory (ROM) 108 in which the unique address of addressable switch 100 is stored.

Digital control device 105 receives control signals at control terminal 106. These control signals include an address and a command. When digital control device 105 senses a control signal at control terminal 106, digital control device 105 compares the address in the received control signal to the unique address stored in ROM 108. If the address contained in the control signal is not the same as the unique address stored in ROM 108, digital control device 105 awaits further control signals. If, on the other hand, the address contained in the control signal is the same as the unique address stored in ROM 108, digital control device 105 executes the command contained in the received control signal or contained in a subsequently transmitted control signal.

In the context of the present invention, addressable switch 100 may perform various tasks in response to an appropriate command received at control terminal 106. For example, digital control device 105 may change the state of load transistor 101 between conductive and nonconductive states by controlling the voltage applied to gate 102. Additionally, digital control device 105 may transmit a reply signal over control terminal 106 indicating the state of load transistor 101 or the unique address stored in ROM 108. By transmitting the state of load transistor 101, digital control device 105 may transmit the status of an attached indicator light. Preferably, digital control device 105 derives <sup>its</sup> power entirely from control line 31 by storing energy in a capacitor (not shown) when control terminal 106 is in a high logic state.

An example of an addressable switch 100 that may be used in the file tracking system of the

present invention is the DS2405 addressable switch available from Dallas Semiconductor, in Dallas, Texas.

Referring again to Fig. 3, branch control points 92a, 92b, ... 92n each include at least one branch control point switch assembly 93a, 93b, ... 93n including a branch control addressable switch 94a, 94b, ... 94n having a unique address associated therewith. Branch control point 92a may also include a branch indicator 95a, which includes a branch indicator light 96a, such as an LED, and a branch indicator addressable switch 97a having a unique address associated therewith to permit independent control of branch indicator light 96a by processor 20.

To communicate with file folder 70a located in a particular drawer 54a, processor 20 transmits a control signal over control line 31 via serial port adaptor 27 to control terminals 106 of all branch control addressable switches 94a, 94b, ... 94n connected to ground line 32. The transmitted control signal includes the unique address associated with branch control addressable switch 94a associated with drawer 54a with which communication is desired. The control signal also includes a command instructing this branch control addressable switch 94a to change to a conductive state thereby providing a connection between ground line 32 and addressable folder switch 76a. Subsequently, processor 20 may transmit control signals individually to addressable folder switch 76a by including the unique address associated therewith. Thus, processor 20 may illuminate folder indicator light 75a of any specified file folder within a specified drawer 54a. Additionally, processor 20 may obtain information from addressable folder switches 76a, 76b, ... 76n through a later described, deterministic process to determine the unique address stored in ROM 108 of each of addressable folder

switches 76a, 76b, ... 76n. Processor 20 may also illuminate branch indicator light 96a by first transmitting a control signal including the unique address of branch control addressable switch 94a and subsequently transmitting a control signal including the unique address of branch indicator addressable switch 97a. By providing a branch indicator light 96a on a folder retainer such as a file drawer 54a, a file tray 40, or a shelving unit 60, one can quickly determine in which folder retainer a selected file folder 70 is located by looking for the folder retainer with the illuminated branch indicator light 96.

In the preferred embodiment, each file folder 70 has an addressable switch having a unique address associated therewith in any given system installation. In some applications, multiple file folders 70 could intentionally have identical addresses corresponding to files related or grouped in some fashion. Further, an inadvertent duplication of addresses could result in any installation from a finite number of addresses in a mass produced, manufacturing environment. In all such situations, unique addresses are still present as envisioned herein.

The manner in which contact can be made between the conductive strips on a file folder 70 and the conductive rails of a bus conductor 80 will now be described with reference to Figs. 5-7.

Bus conductors 80a, 80b, 80c preferably include at least one ground conductive rail 82a, 82b, 82c, a control conductive rail 83a, 83b, 83c, and a support 84a, 84b, 84c for supporting the conductive rails. Support 84a, 84b, 84c preferably is formed of an electrically insulating material and supports the conductive rails in parallel with one another. Bus conductor 80a-80c may be formed as an integral part of a folder retainer or,

alternatively, may be formed as a separate element which may be added to an existing folder  
retainer. As shown in Fig. 5, bus conductor 80a may be implemented in a vertically spaced,  
horizontally extending manner to provide contact along a vertical side, end, or back surface  
of a folder retainer. Thus, using bus conductor 80a, contact may be provided along the back  
5 of a shelving unit or bookcase or along the side of a file or desk drawer. Alternatively, as  
shown in Fig. 6, bus conductor 80b may be implemented such that contact is provided in a  
horizontally spaced, horizontally extending manner along a horizontal or bottom surface of a  
folder retainer. Horizontally extending bus conductor 80b is advantageous in that contact  
with the file folders is aided by gravitational forces and that contact may be made with either  
10 the edges of file folders vertically stacked thereon or with the large exterior surfaces of file  
folders laid flat thereon. Moreover, as shown in Fig. 7, bus conductor 80c may be  
implemented as a support rail in a file drawer 54 upon which hanging file folders 70c may be  
suspended. In such an implementation, file folder 70c does not require conductive strips, but  
rather a file folder indicator light assembly 71 is provided having a contact 78 for contacting  
15 control conductive rail 83c and a wire 77 connected to file folder hanger extension 74, which  
in turn contacts ground conductive rail 82c. However, hanging file folders 70c may still  
have such conductive strips to provide stackability and redundant contact through adjacent  
file folders as is later described.

Bus conductors 80 may optionally be disposed in more than one surface and in  
20 various combinations. For example, one conductive rail may be disposed on the bottom  
interior surface of a file drawer, while another conductive rail may be disposed on an interior  
side surface of the file drawer. Further, one conductive rail may be disposed on the side or



bottom of a file drawer and another conductive rail may be disposed on a support rail, such as that shown in Fig. 7. Additionally, in a shelf or bookcase, one conductive rail could be disposed on a back surface and another could be disposed on a top surface of a shelf.

File folders 70a, 70b preferably include conductive strips including at least one return  
5 conductive strip 72a, 72b and a control conductive strip 73a, 73b arranged in a pattern that allows for relative movement between file folders or between the file folder and a bus conductor, such as that shown in Fig. 5 or that shown in Fig. 6. The conductive strips are preferably applied to both large exterior surfaces as well as made to extend around the side and bottom edges. By applying the conductive strip pattern to both large exterior surfaces of  
10 file folder 70a, 70b, 70c, a file folder 70a, 70b, 70c that is not in direct contact with bus conductor 80a, 80b is nevertheless permitted to have a connection to bus conductor 80a, 80b via adjacent and intermediate file folders 70a, 70b, 70c. Thus, if too many file folders 70a, 70b, 70c are placed in a file drawer 54 such that a file folder 70a, 70b, 70c is laterally  
15 shifted and cannot directly contact bus conductor 80a, 80b a connection will be provided through adjacent file folders 70a, 70b, 70c. Similarly, file folders 70a, 70b, 70c stacked in a file tray 40 will have a connection to bus conductor 80a, 80b via file folders 70a, 70b, 70c positioned therebetween.

As shown in Fig. 5, file folder 70a has at least one large exterior surface having a top and bottom edge as well as left and right side edges. The conductive strip pattern shown  
20 thereon includes three conductive strips (*i.e.*, conductors)--one control conductive strip 73a and two return conductive strips 72a. The control conductor 73a is "V" shaped and includes a first conductive linear strip 73a' extending from the left edge of the surface to a central

point on the bottom edge of the surface and a second conductive linear strip 73a" extending from the central point on the bottom edge of the surface to the right edge of the surface. A first one of the return conductors 72a includes a linear strip 72a' extending in parallel to the first conductive linear strip 73a' of the control conductor 73a from the left edge of the surface to the bottom edge of the surface. The other one of the return conductors 72a includes a linear strip 72a" extending in parallel to the second conductive linear strip 73a" of the control conductor 73a from the bottom edge of the surface to the right edge of the surface. The linear strips of the two return conductors 72a are positioned an equal distance on opposite sides of the control conductor 73a. Preferably, the same conductive strip pattern is applied to the back or other exterior surfaces of file folder 70a.

As shown in Fig. 6, file folder 70b also has at least one large exterior surface having a top and bottom edge as well as left and right side edges. The conductive strip pattern shown thereon includes three conductive strips--one control conductive strip 73b and two return conductive strips 72b. The control conductor 73b consists of a conductive linear strip extending from the top edge of the surface to a bottom edge. The return conductors 72b are formed of two linear strips 72b' and 72b", each extending in parallel to the conductive linear strip of the control conductor 73b from the top edge to the bottom edge. The two linear strips 72b', 72b" constituting the return conductors 72b are positioned an equal distance on opposite sides of the control conductor 73b. Preferably, the same conductive strip pattern is applied to the back or other exterior surfaces of file folder 70b.

The conductive strip patterns shown in Figs. 5 and 6 permit proper electrical contact even when the file folders 70a, 70b are rotated 180° about the illustrated y axis, which

parallels the left side edges of the file folders, relative to one or more adjacent file folders or relative to bus conductor 80a, 80b. The conductive strip pattern shown in Fig. 5 may be utilized with either of the bus conductors 80a, 80b shown in Figs. 5 and 6 because the strips overlap or extend around both the bottom and side edges of the file folder and permit proper electrical contact even when a file folder 70a is rotated 90° about the z axis, which is orthogonal to the large exterior surfaces of file folders 70a, 70b, with respect to adjacent file folders or bus conductor 80a, 80b. Further, the conductive strip pattern shown in Fig. 5 permits contact when laid flat on an adjacent file folder or an appropriately arranged bus conductor.

The conductive strip pattern shown in Fig. 6 is similarly advantageous in that proper electric contact may be made regardless of whether contact is made with the edge of file folder 70b or with the entire surface of file folder 70b should file folder 70b be laid flat on conductive bus 80b. Thus, with respect to bus conductor 80b or an adjacent file folder, file folder 70b may be rotated 180° about the x, y, and z axes, and further may be rotated 90° about the x axis, which parallels the bottom edges of file folders 70a, 70b, without disrupting the electrical contact between bus conductor 80b and the conductive strips. Additionally, the conductive strip pattern shown on file folder 70b permits file folders 70b to be significantly laterally shifted in the y direction relative to one another while still maintaining the necessary contact.

Hence, the conductive strip patterns are configured to electrically connect an addressable folder switch 76 with electrical contacts of the file tracking system when the file folder is positioned in any one of several different positions that allow a proper connection to

be made. Further, the conductive strip patterns are configured to electrically connect an addressable folder switch 76 with the file tracking system when the file folder 70 is positioned in (1) any one of several different orientations with respect to the electrical contacts of the electronic file tracking system; (2) any one of several different lateral positions with respect to an adjacent file folder; or (3) any one of several different rotated positions with respect to an adjacent file folder. Additionally, the conductive strip pattern is preferably configured to electrically connect the addressable folder switch 76 to the file tracking system at a plurality of locations on the file folder 70.

The conductive strips may be formed of conductive tape, fabric, coating, which may be a conductive ink or polymer, or other suitable conductive materials. The choice between such materials being a factor of the shape and composition of the particular file folder, cost and longevity goals, and other concerns.

As evident from the foregoing description of the bus conductors and the conductive strip patterns applied to the file folders, the file tracking system of the present invention offers exceptional flexibility, both in design and in use.

Having described the preferred structure of the first embodiment of the present invention, the operation of file tracking system 10 will now be described with reference to Figs. 8-13.

Fig. 8 shows a main user interface window 200 that a user would see on display 22 of processor 20. Main user interface window 200 indicates the title 201 of a file identified in the database, the content and keywords of the file 202, the location of the file 203, the originator of the file 204, the date the file was filed in the system 205, the name of the last

user of the file 206, the date the file was last removed from the system 207, and the date the file was returned to the system 208. The database may store additional information for display to the user. For example, the database may store the locations in a computer network where any redundant copies of the file are stored.

5           The software utilized in file tracking system 10 generally includes a user interface module for providing windows, dialog boxes, and menus, such as window 200. Preferably, the user interface module operates in a graphic user interface such as Windows® software available from Microsoft Corporation. The software also includes several standalone event subroutines that are executed when their associated controls are activated by a user or for  
10           timed events, at the configured intervals. The event subroutines may be classified into four main functional groups: a database interface; a bus interface; option control; and Debug control.

          The database interface subroutines provide the viewing, editing, and search capability for the file folder records. The viewing controls allow movement through the database records and the display of record fields. The editing controls allows the entry, deletion, and  
15           updating of database records. The search controls let the user locate records by value within the title or content\keyword field, and the viewing of the searched group.

          The bus interface subroutines compile and issue control signals over bus 30 to the various branch control point switch assemblies 93 and file folders 70 on the system. An  
20           example of an interface for a single pair bus having addressable switches 100 connected thereto is TMEX™ interface available from Dallas Semiconductor, Dallas, Texas. Preferably, the bus interface includes functions to start and stop a communication session,

identify attached devices, and ~~the~~ sense and control the functioning of the addressable switches.

The option control subroutines allow the user to adjust the indicator light blink rate, the indicator light ON duration, bus scan rate, device persistence, and form display to include debug information. A user may set the indicator light blink rate and the bus scan rate by defining the period between their events, which is the interval property of their timer control. The user may set the device persistence in increments of bus scan rate and controls the length time that passes before processor 20 considers a missing file folder device to be removed. This persistence compensates for intermittent contacts during file folder movement. The debug information includes a status window used to display program messages, access to debug controls, and database fields not normally of interest to the user such as state variables and the unique address associated with the device.

The debug controls allow the status messages to be cleared, the bus to be reset, and the scan timers to be enabled/disabled. Fig. 9 shows a debug window 210 illustrating the manner in which the user interface presents the debug controls to a user.

The operations described below, utilize various combinations of the event subroutines described above. Thus, any given operation may include one or more data interface subroutine, bus interface subroutine, option control subroutine, and/or debug control subroutine.

Fig. 10 shows a polling rate request window 215, which allows a user to adjust the rate at which file tracking system 10 polls the file folders located within the system. A user

may display the polling rate request window 215 by selecting the "Options" menu on main user interface window 200.

With the exception of the ability to adjust the polling rate, processor 20 generally polls file folders 70 and maintains the database transparently to the users. The manner by which processor 20 periodically polls file folders 70 will be described with reference to the flow charts shown in Figs. 11 and 12.

Polling (Step 300) occurs periodically at the rate established by the user in polling rate request window 215. Initially, processor 20 executes a scan of a main branch looking for new, reconnected, and removed branch control point switch assemblies 93 (Step 302). The manner by which processor 20 performs this operation is shown in the flow chart in Fig. 12.

Processor 20 initiates a scan 302, 330 by opening communication with the desired main branch 98 (Fig. 2) (Step 304). Then processor 20 attempts to detect the presence of a device (in this case a branch controller addressable switch) (Step 306). By a process of elimination, processor 20 may determine the unique address of any newly detected branch controller addressable switch 94 and store the unique address in the database. If a branch controller addressable switch 94 is found, processor 20 queries whether branch controller addressable switch 94 is new by accessing the database and determining whether a branch controller addressable switch 94 having the received unique address was previously registered therein (Step 308). If the branch controller addressable switch 94 detected is new, processor 20 adds the branch controller addressable switch 94 to the database and automatically fills in

whatever fields can be filled in with the information that may be obtained such as the location of branch controller addressable switch 94 (Step 310).

To determine the unique address of devices, such as addressable folder switches 76 and branch controller addressable switches 94, located on a given branch, processor 20 issues a command instructing the addressable folder switches 76 and branch controller addressable switches 94 to transmit the unique address stored in ROM 108 bit by bit. When a plurality of devices are present on the activated branch, each of them simultaneously transmits the first bit of the unique address on bus 30. Processor 20 senses the state of bus 30, which represents a logical AND of all the first bits of each device located on the activated bus. Processor 20 then issues a command to each device to transmit the complement of the first bit of their respective unique address. If processor 20 detects two "0's" in response to these two *inquiries* ~~inquiries~~, processor 20 determines that there are devices located on the branch that have a "0" in the first bit position and other devices having a "1" in the first bit position. If all devices had a "0" in the first bit position, the reading would have been a "0" followed by a "1". If a "1" followed by a "0" were received, processor 20 determines that all the present devices have a "1" in the first bit position. Last, if processor 20 detects two "1's", no devices are present on the activated branch.

The above procedure for identifying unknown devices on a branch may be further optimized by first disabling all known devices on the branch and then performing the operation on those devices that are not disabled. In the illustrated embodiment, such procedure is carried out using the SearchROM command included with the TMEX Software from Dallas Semiconductor.



Processor 20 then issues a control signal including one of the "1" or "0" logic values in the first bit position in order to disable the devices that do not have this logic value in the first bit position of their unique address. Processor 20 then issues a command to the devices that remain enabled requesting these devices to transmit the second bit of their unique  
5 addresses and the complement thereof. Processor 20 then uses the same process to determine the value of the second bit of at least one of the remaining devices. Processor 20 repeats the above steps until the unique address of one of the devices is known.

Subsequently, processor 20 reactivates the other devices on the activated branch and repeats the above process using a different logic level at the highest bit position where  
10 processor 20 was able to determine that a single device remained. In this manner, processor 20 determines the unique address of each file folder 70 and branch controller 93 located on an activated branch.

After the new branch controller addressable switch 94 has been added to the database,  
15 processor 20 scans the rest of main branch 98 looking for additional branch controller addressable switches 94 (Step 306). If processor 20 detects a branch controller addressable switch 94 on the main branch 98 that is not new, processor 20 compares the branch controller state and location with that previously stored in the database and updates the database if any changes are detected (Step 312). Processor 20 continues to search for additional branch controller addressable switches 94 on main branch 98 until no further  
20 branch controller addressable switches 94 are detected in Step 306.

When processor 20 determines that no further branch controller addressable switches 94 are present on main branch 98, processor 20 closes communication with main branch 98

(Step 314). Next, processor 20 queries the database for the number of branch controller addressable switches 94 presently registered in the database as being located on main branch 98 (Step 315) and compares this number with the number of branch controller addressable switches 94 that processor 20 detected in Step 306 while scanning main branch 98 (Step 316). If the number of branch controller addressable switches 94 presently registered exceeds the number of branch controller addressable switches 94 detected, processor 20 determines that at least one branch controller addressable switch 94 has been removed from main branch 98.

To verify that a branch controller addressable switch 94 has been removed, processor 20 reopens communication with main branch 98 (Step 318) and transmits control signals to each branch controller addressable switch 94 registered in the database by including the unique address thereof in the control signal, which is stored in the database (Step 320). If a branch controller addressable switch 94 fails to respond to the control signal sent by processor 20, processor 20 changes the state of the branch controller addressable switch 94 registered in the database to "timing out" (Step 322). After processor 20 transmits a control signal to each registered branch controller addressable switch 94, processor 20 closes communication with main branch 98 (Step 324).

After processor 20 has closed communication with the reopened main branch 98 in Step 324 or after processor 20 has determined that the number of branch controller addressable switches 94 registered in the database does not exceed the number of branch controller addressable switches 94 detected in Step 316, processor 20 queries the database for the identity and unique address of all present branch controller addressable switches 94 on

the main branch 98 (Step 326 in Fig. 11) and changes the state of addressable branch controller switches 94 to conducting one at a time in order to activate each secondary branch 99 (Step 328).

5 While a branch controller addressable switch 94 is conducting, processor 20 scans the activated branch for new, replaced, or removed file folders 70 contacting the activated branch (Step 330). The manner by which processor 20 performs this operation is shown in the flow chart in Fig. 12.

10 First, processor 20 opens communication with the desired secondary branch 99 (Step 304). Then processor 20 attempts to detect the presence of a device (in this case a file folder 70) (Step 306). If a file folder 70 is found, processor 20 queries whether file folder 70 is new by accessing the database and determining whether file folder 70 was previously registered therein (Step 308). If the file folder 70 detected is new, processor 20 adds file folder 70 to the database and automatically fills in whatever fields can be filled in with the information that may be obtained (Step 310). By the process of elimination, processor 20 may determine the unique address of any newly detected addressable file folder switch 76 and store the unique address in the database. After the new file folder 70 has been added to the database, processor 20 scans the rest of the opened secondary branch 99 looking for additional file folders 70 (Step 306).

20 If processor 20 detects a file folder 70 on the opened secondary branch 99 that is not new, processor 20 compares the file folder state and location with that previously stored in the database and updates the database if any changes are detected (Step 312). Processor 20

continues to search for additional file folders 70 on secondary branch 99 until no further file folders 70 are detected in Step 306.

When processor 20 determines that no further file folders 70 are present on the opened secondary branch 99, processor 20 closes communication with this secondary branch 99 (Step 314). Next, processor 20 queries the database for the number of file folders 70 presently registered in the database as being located on this secondary branch 99 and compares this number with the number of file folders 70 that processor 20 detected in Step 306 while scanning the secondary branch 99 (Step 316). If the number of file folders 70 presently registered exceeds the number of file folders 70 detected, processor 20 determines that at least one file folder 70 has been removed from the opened secondary branch 99.

To verify that a file folder 70 has been removed, processor 20 reopens communication with the secondary branch 99 (Step 318) and transmits control signals to each file folder 70 registered in the database by including the unique address thereof in the control signal, which is stored in the database (Step 320). If a file folder 70 fails to respond to the control signal sent by processor 20, processor 20 changes the state of the file folder 70 registered in the database to "timing out" (Step 322). After processor 20 transmits a control signal to each registered file folder 70, processor 20 closes communication with this secondary branch 99 (Step 324).

After processor 20 has closed communication with the reopened secondary branch 99 in Step 324 or after processor 20 has determined that the number of file folders 70 registered in the database does not exceed the number of file folders 70 detected in Step 316, processor 20 activates another secondary branch 99 by transmitting a control signal including the

unique address of the branch controller addressable switch 94 associated with the selected secondary branch 99 (Step 328 in Fig. 11).

After processor 20 has scanned all the secondary branches 99, processor 20 queries the database for the identity of all devices in the "timing out" state (Step 332) and decrements the persistence values stored in association therewith (Step 334). The persistence value indicates the number of additional times that processor 20 will perform a scan of all file folders 70 before a file folder having a "timing out" status will be considered to have a "timed out" or removed status. When a file folder has "timed out" (Step 336), processor 20 updates the database to indicate this change in status (Step 338) and ends the scanning operation (Step 340). Once the scanning operation is finished, a timer is started to determine when the next scanning operation is to be performed.

Processor 20 automatically updates the database by inserting the date and time the file was detected as having been removed from the system into the appropriate database fields associated with file folder 70. Additionally, processor 20 may identify the individual who removed file folder 70 by determining who was the last individual to log onto the system and cause the indicator light of the removed file folder to blink. This is especially helpful in locations where security measures require logging onto the system before removing files. Then, if the presence of the removed file folder 70 is subsequently detected at a different location, such as on an individual's desk, processor 20 may update the database to indicate that the individual who removed the file is the individual associated with the location (*i.e.*, desk) where file folder 70 was subsequently detected or have a separate field corresponding to the individual responsible for that particular area or location.

By actively polling each file folder 70, file tracking system 10 maintains an accurate record of file folder location and usage history without requiring action by office personnel. Moreover, office personnel need not spend their valuable time keeping the files organized. Using file tracking system 10, a person may quickly determine the present location of a file folder and cause LEDs on the file folder and file cabinet drawer to blink to allow the person to quickly identify the requested file folder. Because of the ease by which a person may locate a file folder, office personnel may place the file folders anywhere and in any convenient order. Thus, office personnel may place the most frequently used file folders at the front of a file drawer where they are more easily accessed at a later time. Furthermore, because new file folders may be placed in any file drawer or on any shelf, there is no need to rearrange the file folders to make room for new file folders.

In addition, by utilizing a database to index file folders, the file folders may be physically grouped or classified into various topical groups and subgroups. Thus, a user may access all the file folders constituting the group or subgroup. Moreover, by issuing an appropriate command, a user can cause the indicator lights on all the file folders of a selected group of file folders to blink thereby adding to the ease by which the user can locate the physical file copies for immediate use or to gather for placement into a desired storage pattern or location. Similarly, a user can locate all files mentioning a particular subject by performing a keyword search. Thus, the present invention may provide higher levels of file organization even if a user wishes to maintain the files in a specific nonrandom order.

Fig. 13 is a flow chart illustrating the operation of file tracking system 10 when operating in an indicator light scanning operation. As will be apparent from the following

description, the indicator light scanning operation is useful for causing the indicator lights on the selected file folders and branch indicators to blink.

An indicator light scanning operation is performed at timed intervals (Step 400).

Processor 20 begins the operation by querying the database for all present branch controller  
5 addressable switches 94 on the main branch (Step 402). Then, for each branch controller  
addressable switch 94 that is present (Step 404), processor 20 queries the database for file  
folders 70 having an indicator light blink flag set to logic "1" and located on the branch  
controlled by the selected branch controller addressable switch 94 (Step 406). The indicator  
light blink flag for a file folder is set when a user requests processor 20 to blink the indicator  
10 light of a selected file folder. If no file folders are found that are connected to the selected  
branch (Step 408) and have their indicator light blink flag set to "1", processor 20 selects the  
next branch (Step 404). If the processor 20 finds file folders 70, processor 20 queries the  
database for branch indicators on the selected branch (Step 410), then processor 20 opens  
communication with the selected branch (Step 412) and transmits control signals to each  
15 branch indicator 95 that is found on the selected branch (Step 414) causing the branch  
indicator lights 96 to toggle on and off (Step 416). Next, processor 20 transmits control  
signals to each file folder 70 that is found on the selected branch having its indicator light  
blink flag set to "1" (Step 418) causing the folder indicator lights 75 to toggle on and off  
(Step 420). After all of the folder indicator lights 75 on the selected branch have been  
20 toggled, processor 20 closes the selected branch (Step 422) and selects the next branch (Step  
404). The process is repeated until there are no more branches to select (Step 424). This  
procedure may be programmed to be executed several times per second.

The control signals transmitted by processor 20 to toggle the indicator lights may include a first control signal containing the unique address of the addressable device followed by a second transmitted control signal including a command to toggle the indicator light. Alternatively, the control signals may include a single control signal transmitted by processor 5 20 that includes both the unique address and the command to toggle the indicator light.

Although the above procedure is presently used to blink the indicator lights, it is also possible to utilize indicator lights that blink upon receiving an instruction to do so until a subsequent instruction is received to stop blinking. Further, processor 20 may read each indicator for the status of the indicator light prior to issuing a control signal causing the 10 indicator light to blink in order to ensure that the indicator light is not already turned on.

Fig. 14 shows a file tracking system 500 constructed in accordance with a second embodiment of the present invention.

The second embodiment of the file tracking system 500 differs from the first embodiment only in that file tracking system 500 includes a plurality of processors 20a-20d 15 interconnected by a network, such as a local area network (LAN) 91 or a local office network (LON). An example of a LON in which the present invention may be implemented is disclosed in U.S. Patent Application Serial No. 08/165,029, the disclosure of which is incorporated by reference herein. Each processor may store a portion of the entire database of the system such that the various processors and their respective portions of the database 20 constitute a distributed database system 501. In such a system any one of processors 20a-d may access the database stored in any other processor using a conventional distributed



database management system (DDBMS), a networked database server, or through database information stored with the file folder.

The DDBMS architecture of tracking system 500 allows any single file tracking program to operate on records that are spread across multiple databases that are running on a variety of different processors and operating systems connected through a variety of communication networks. In a networked database server, a single processor maintains a central database with the other processors having a subset copy of the records pertaining to the file folders local to each processor. A processor would use this local copy to monitor the file folder state and indicator light state, and relay only changes in state back to the central database.

By scaling the file tracking system of the present invention to permit multiple access to the system at various locations, file tracking system 500 permits multiple users in various locations to locate file folders that are in distributed locations about the organization. Thus, this system can easily be adapted for use in a large organization having numerous office buildings in which file folders may be located in any office or file repository of these office buildings.

Although the above embodiments of the present invention have been described as using physical connections between the various elements, any one or all of the above connections may be replaced with a radio link by providing a radio frequency (RF) transceiver connected to processor 20 and RF transceivers on the folder retainers and/or the file folders themselves. Fig. 15 shows a third embodiment using RF signals. The third embodiment differs from the second embodiment in that RF transceivers 120 are connected

to processor 20 and either to each file folder 70 or to each folder retainer, which refers to tray 40, file cabinet 50, shelving unit 60, and desk drawer 86. The third embodiment may utilize the same RF communication protocols as used in cellular telephones. For example, the system may employ cellular digital packet protocol (CDPP) or the protocol used for personal communication systems (PCS). These protocols may be employed by utilizing branch controllers as a cell base station whereby file folders located within each cell register with the closest cell base station such that processor 20 may track the location of each file folder.

Although the embodiment shown illustrates a system utilizing all RF links from processor 20, a combination of RF links and physical bus connections may also be employed. By providing the availability of radio links, mobile folder retainers, such as file carts, as well as remotely located folder retainers may be employed in the file tracking system of the present invention.

Although the processor(s) of the present invention have been described with reference to personal computers, the processor may be a processor embedded in or near the folder retainer. In such an arrangement, it may be preferable for the embedded processor to include a plurality of serial ports to which different branches of the bus may be connected, thus, eliminating the need for a number of branch controllers. Further, the processors may be computer terminals connected to a network.

Further, processor 20 may be implemented in either a single processing unit or in a distributed system whereby various tasks performed by processor 20 are allocated to various components of the distributed system. For example, one component may be responsible for

scanning the bus, while another may be used to provide an interface with the users. Further, various tasks described above as being performed by processor 20 may be allocated to embedded processor 27. For example, embedded processor 27 may maintain separate databases identifying which file folders are located on their associated branch.

5           Additionally, other types of annunciators or, as more broadly defined herein, file locating devices, such as an audible alarm, may supplement or replace the visual indicator lights used in the file tracking system.

Although it is preferable that the present invention be practiced using addressable  
n devices that each have ~~a~~ unique addresses associated therewith, it is possible that in a system  
10 employing a large number of addressable devices, two or more addressable devices could  
have the same address. The present claims are intended to cover the situation where at least  
a plurality of addressable devices have unique addresses. To ensure such coverage, some  
claims below recite that the addressable devices have a substantially unique address.

The foregoing description of preferred embodiments of the invention has been  
15 presented for purposes of illustration and description. It is not intended to be exhaustive or  
to limit the invention to the precise form disclosed, and modifications and variations are  
possible in light of the above teachings or may be acquired from practice of the invention.  
The embodiments were chosen and described in order to explain the principles of the  
invention and its practical application to enable one skilled in the art to utilize the invention  
20 in various embodiments and with various modifications as are suited to the particular use  
contemplated. It is intended that the scope of the invention be defined by the claims  
appended hereto, and their equivalents.